

## JBC WAREHOUSE

Copper= 3ea 10ft 3" of DWV and 7ea 10ft 4" of L Copper Pipe  
Fittings= Couplings, Elbows, Street Elbows, Sizes= 3-1/2", 2-5/8,  
4-1/8, TEE=3" X 3" X 2-1/2, Couplings 3" FMP X 3" SW

Brass= Nut Compression 5/16, Elbows= (3/8 M Flare X 1/8)  
(1/8 X 1/8 MPT) (3/16 Flare X 1/8 MPT)(Flare Nut 1/8)  
(Bushing 3/8 X 1/8)(Elbow 45DEG 1/4 X 1/8)(Sleeve  
Compression 1/2") (NUT Compression 1/4)  
(Elbow 3/4 FL X 1/2 MPT)(Union Compression 5/16)(Elbow  
3/8 FPT)(Connector Compression 1/4 X 1/4 FPT)(Elbow  
Compression 5/16)(Union Elbow Compression 3/8)

Steel Blind Flange 5" and 10"

PVC, = (S/80 Tee 2") (S/40 Tee 2 X 2 X 1)(S/40 Elbow 2") (S/40  
Elbow 45- 2")

Coupling For Wire Tray Plate # 68-02 RC

FUSE= (Limiter KAF 300A 600V)(Limiter KAF 800A  
600V)(Limiter KAF 500) (TYPE EJ-1.5E AMP 8.5" 5.5KV 60HZ)  
(TYPE EJ-1.5E AMP 11.5" 14.4KV 60HZ)(130V 200A) (130V  
400A)(250V 8A)(5000V 1/8A)(600V 100A)(600V 10A) (3000V  
10A, 12"L) (Diffuser Pump Connector) (Fuse 500A 130V DC Bias)