

REVISIONS				
SYM.	ZONE	DESCRIPTION	DATE	APP.
C		Issued all design changes as Rev C (TIO)	4/19/07	SAB

C	100.410.000	REV.
	SH. NO. 1 OF 1	C

NOTES:



1. PRIOR TO INSTALLATION, THOROUGHLY CLEAN SHAFTS (ITEM 2).
REMOVE OIL AND GREASE.

QTY.: 1 PER LINEAR GUIDE

4	-	10-32 x 5/8 St. St. Sock. Hd. Cap Scr.	2			316 Stn. Steel, Dicronited	C
3	-	#10 St. St. Spring Lock Washer	2			316 Stn. Steel	C
2	100.410.002	SHAFT	2				C
1	100.410.001	GUIDE BASE	1				C

	ITEM	DWG. NO.	DESCRIPTION	G1	G2	G3	REMARKS	REV.
				QUANTITY				

PRINT DISTR.	PLOT DATE: 4/19/2007 CAD FILE NAME: 100-410-000.idw
-----------------	--

100.410.000 SH. NO. 1 OF 1	UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES; TOLERANCES ON: .00 ± .010 .000 ± .005 FRACTIONS ± 1/64 ANGLES ± 0.5° ALL SURFACES: 	CORNELL UNIVERSITY		 LEPP		CORNELL UNIVERSITY Floyd R. Newman Laboratory Ithaca, NY 14853									
		75 kW CW INPUT COUPLER, LINEAR GUIDE SHAFTS ASSEMBLY													
		CHECKED BY: VGV		DRAWN BY VM		DRAWN FOR SAB		DATE 1/22/2006		SCALE 1:1		C		100.410.000 SH. NO. 1 OF 1	
APPROVED BY: SAB															